

Sentry V Series Digital Video Recorder

V Series DVR

- Supports up to 32 cameras
- Up to 30fps/camera recording and display
- PTZ and POS enabled
- Hybrid Compatible



Features

- 4 to 32 channel models
- Simple, plug and play installation
- Selectable recording resolution
- Up to 30 frames/second total recording and display
- Remote setup and configuration available
- Simultaneous viewing, recording, playback and remote access
- PTZ and POS enabled
- 1 year warranty and 1 year free technical support included with optional 5 year warranty available
- Remote monitoring and recording
- Remote access via iPhone™, Blackberry™ and Android™ Phones
- Hybrid Compatible

Description

These all-in-one digital video surveillance solutions are designed to process video, audio and data from local and remote networked surveillance environments. Systems feature powerful networking and quality transmission, enabling remote access to surveillance sites using remote applications or smartphones. The V Series DVR is also designed to simplify the integration of Point-of-Sale and Central Monitoring Systems.

The Sentry V Series digital video recorder (DVR) supports up to 32 cameras as well as up to 30fps/camera recording and display. Based on the GV series video capture cards, the V Series DVR provides a superb digital video surveillance solution. The digitally recorded video is optimally compressed, yet retains excellent image quality.

For more information on any of our products or services please visit us on the Web at:

www.sentry-resellers.com

or

www.cctvsentry.com



Sentry V Series Digital Video Recorder- Specifications

SENTRY V SERIES DVR SPECIFICATIONS – V650-V800		
MODEL	V650	V800
Chassis	Compact, Rugged Case	
Video Inputs	4 - 32	4 - 32
Audio Inputs	2-4	4-8
Video Compression	Geo MPEG4, Geo MPEG4 (ASP), Geo H264, Geo H264 V2	
Recording Resolution	320x240, 640x240, 640x480, 720x240, 720x480	
Total Recording/ Display Speed	60 frames/sec – up to 16 120 frames/sec - 32	120 frames/sec – up to 16 240 frames/sec - 32
Remote Access	TCP/IP, LAN, WAN, Internet. iPhone™, Android™ and Blackberry™ remote access also supported.	
Event Recording	Continuous, Video motion, Schedule or Alarm sensing	
Monitor Output	1 SVGA Port	
Approx Hard Drive Usage (30%)	3.6GB/day*	7.2GB/day*
Software	Windows™ 7, GV-MultiCam System and System Restore Software	
Hardware	Intel™ brand processor, LAN adapter, keyboard, mouse	
Video Backup Device	DVD-RW/CD-RW drive	
Standard Storage	1TB (32ch models come with 2TB of Standard Storage)	
Standard Warranty	1 year parts and labor, 1 year toll free technical support. Extended warranties available.	

SENTRY V SERIES DVR SPECIFICATIONS – V1120-V1480			
MODEL	V1120	V1240	V1480
Chassis	Compact, Rugged Case		4U Rackmount Case
Video Inputs	8, 16, 32		16, 32
Audio Inputs	8, 16, 32		16, 32
Video Compression	Geo MPEG4, Geo MPEG4 (ASP), Geo H264, Geo H264 V2		
Recording Resolution	320x240, 640x240, 640x480, 720x240, 720x480		
Total Recording/ Display Speed	120 frames/sec – 8, 16 240 frames/sec - 32	240 frames/sec – 8, 16 480 frames/sec - 32	480 frames/sec – 16 960 frames/sec - 32
Remote Access	TCP/IP, LAN, WAN, Internet. iPhone™, Android™ and Blackberry™ remote access also supported.		
Event Recording	Continuous, Video motion, Schedule or Alarm sensing		
Monitor Output	1 SVGA Port, 1 TV Output		
Approx Hard Drive Usage (30%)	From 7.2GB/day*	From 14.4GB/day*	From 28.8GB/day*
Software	Windows™ 7, GV-MultiCam System and System Restore Software		Windows™ 7 software installed on solid state drive, GV-MultiCam System and System Restore Software
Hardware	Core 2 Quad Processor, LAN adapter, keyboard, mouse		
Video Backup Device	DVD-RW/CD-RW drive		
Standard Storage	1TB (32ch models come with 2TB of Standard Storage)		
Standard Warranty	1 year parts and labor, 1 year toll free technical support. Extended warranties available.		

For more information on any of our products or services please visit us on the Web at:
www.sentryresellers.com
 or
www.cctvsentry.com